



# 2025 PRODUCT OVERVIEW

Elphinstone Mining Solutions  
[elphinstone.com](http://elphinstone.com)

**ELPHINSTONE**





# E10 AND E15 CONFIGURABLE BASE PLATFORMS

## Wide range of applications

The Elphinstone E10 (10-tonne\*) and New E15 (15-tonne\*) are modular and configurable base platforms with a high level of interchangeability of parts and components between both machines. The E10 (formerly WR810) can be configured as 6m³ agitator, delivery with crane, flat deck, Elevated Work Platform (EWP) or scissor lift, fuel and lube truck, water tank, water cannon and others.

The E15 range includes 7m³ agitator, delivery with crane, flat deck, water tank, and fuel & lube. Additional models will be released in the future.

## Common engine front frame

Common to both the E15 and E10 range, the engine front frame can accommodate either Cat C7.1 Tier 3 or Tier 4 Final engine arrangements featuring Caterpillar's breakthrough ACERT™ Technology to meet exhaust emission reduction standards. Both cab configurations feature 3-person seating, climate-controlled air conditioning, ergonomic central driving position with a clear 180-degree view, and dial controller for the retarder, speed and implement controls.

## Electromagnetic retarder and speed control

Fitted as standard to the rear frame on both E10 and E15 platforms is a high-capacity electromagnetic retarder which provides superior braking performance on grade, and diagnostic capabilities with alarm and fault conditions reported back to the 12-inch touch screen operator display. Both platforms also feature "speed control" whereby the operator can set a speed and the machine will use the engine speed, transmission and retarder to maintain that speed.

## Oscillating hitch

The oscillating hitch ensures 4-wheel ground contact and reduced wear on the hitch and steering components. Nitrogen-charged hydraulic suspension cylinders and A-frame provide superior front axle ride quality over rough terrain.

*\*Nominal base capacity. Can vary depending on configuration.*

## E15 Delivery

### Machine Application

A flexible transport solution with lift on or lift off capability ideal for moving parts, components, equipment, and maintenance personnel safely and securely throughout the mine site. The large flat deck has the capacity to fit 6 standard size pallets.

### Standard features:

- » Cat powertrain.
- » All wheel drive with lock-up torque converter.
- » Low-profile (2.4 m high) ROPS/FOPS certified front-mounted three seat cab.
- » Enclosed operator station with pressuriser and air conditioning.
- » 12" digital touch screen operator display.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Oscillating hitch.
- » Front suspension.
- » Secondary steering and recovery brake release system.
- » Electromagnetic retarder (High-capacity).
- » Electronic speed control.
- » Air-cooled compartment, cupholders and device charging ports.
- » HIAB crane with rated lift capacity of 8.8 TM.
- » Crane outreach 7.7 m.
- » Automatic crane pack up.

- » Crane incorporates manually extendable stabiliser legs with levelling sensors.
- » Crane controlled via manual lever control or wireless joystick remote control.
- » Crane includes programmed exclusion zones.
- » Deck size 4.5 m x 2.5 m with maximum payload 16,620 kg.
- » Cameras - multiple viewing options available.
- » Wheel chocks.

### Optional features:

- » DPF exhaust muffler on Tier 3.
- » High speed fluid change.
- » Cat C7.1 TIER 4F engine arrangement.
- » Front and rear hydraulic jacks.
- » Fire suppression system.
- » Automatic lubrication system.
- » Hydraulic filled nitrogen-charged front suspension.

## Specification Snapshot

GVM	35,860 kg
Maximum payload	16,620 kg
Engine model	Cat C7.1 ACERT™ TIER 3
Gross power	SAE J1995 168kW / 228 hp
Articulation	42.5°
Tyres	16.00 R20





## E15 Agitator 7m<sup>3</sup>

### Machine Application

Specialising in the transport of shotcrete or concrete to backfill voids, this agitator has outstanding ride and handling at any speed, full or empty for lower cycle times and greater productivity. Onboard mixing and loading via chute or conveyor.

#### Standard features:

- » Cat powertrain.
- » All wheel drive with lock-up torque convertor.
- » Low-profile (2.4 m high) ROPS/FOPS certified front-mounted three seat cab.
- » Enclosed operator station with pressuriser and air conditioning.
- » 12" digital touch screen operator display.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Oscillating hitch.
- » Front suspension.
- » Secondary steering and recovery brake release system.
- » Electromagnetic retarder (High-capacity).
- » Electronic speed control.
- » Air-cooled compartment, cupholders and device charging ports.
- » 7m<sup>3</sup> agitator bowl including 2x access covers and 2x empty bowl lift points.
- » Digital slump meter reading in cab.

- » Agitator bowl motor fitted with quick connect couplings.
- » Transit bowl speed 0-6 rpm.
- » Plant mix bowl speed 0-19 rpm.
- » Bowl guards with 4x access covers for maintenance.
- » Fill chute camera
- » Reverse camera.
- » Wheel chocks.

#### Optional features:

- » DPF exhaust muffler on Tier 3.
- » High speed fluid change.
- » Cat C7.1 TIER 4F engine arrangement.
- » Front and rear hydraulic jacks.
- » Manual slump gauge at the rear of the machine.
- » High pressure washdown system.
- » Low pressure high volume for bowl wash.
- » Form oil tanks and spray lance.
- » Onboard chemical additive system.
- » Manual hand pump to add chemicals direct to bowl.
- » Discharge chute camera.
- » Fire suppression system.
- » Automatic lubrication system.
- » Hydraulic filled nitrogen-charged front suspension.

### Specification Snapshot

GVM	35,860 kg
Volume	7 m <sup>3</sup>
Engine model	Cat C7.1 ACERT™ TIER 3
Gross power	SAE J1995 168kW / 228 hp
Articulation	42.5°
Tyres	16.00 R20

## E10 Delivery

### Machine Application

A flexible transport solution with lift on or lift off capability ideal for moving parts, components, equipment, and maintenance personnel safely and securely throughout the mine site. The large flat deck has the capacity to fit 6 standard size pallets.

#### Standard features:

- » Cat powertrain.
- » All wheel drive with lock-up torque convertor.
- » ROPS/FOPS certified centre-mounted three seat cab [3 m high].
- » Tilting cab.
- » 12" digital touch screen operator display.
- » Swing out radiator grill.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Hinged bonnet and exhaust module.
- » Oscillating hitch.
- » Secondary steering and recovery brake release system.
- » Electromagnetic retarder.
- » Electronic speed control.
- » Automatic crane pack up.
- » HIAB crane with rated lift capacity of 8.8 TM.
- » Crane outreach 7.7 m.
- » Automatic crane pack up.
- » Crane incorporates manually extendable stabiliser legs with levelling sensors.

- » Crane includes programmed exclusion zones.
- » Crane controlled via manual lever control or wireless joystick remote control.
- » Deck size 3.7 m x 2.5 m
- » Cameras - multiple viewing options available.
- » Wheel chocks.

#### Optional features:

- » Enclosed operator station with air conditioning.
- » Cab pressuriser.
- » DPF exhaust muffler on Tier 3.
- » Front suspension.
- » High speed fluid change.
- » Cat C7.1 TIER 4F engine arrangement.
- » Fire suppression system.
- » Automatic lubrication system.

### Specification Snapshot

GVM	28,760 kg
Maximum payload	11,130 kg
Engine model	Cat C7.1 ACERT™ TIER 3
Gross power	SAE J1995 168kW / 228 hp
Articulation	42.5°
Tyres	14.00 R20





## E10 Scissor Lift

### Machine Application

A purpose-built underground elevated work platform (EWP) with 17% levelling capability utilising hydraulic jacking legs. Ideal for the safe transportation and installation of large components and services into the ceiling of the mine.

#### Standard features:

- » Cat powertrain.
- » All wheel drive with lock-up torque convertor.
- » ROPS/FOPS certified centre-mounted three seat cab [3 m high].
- » Tilting cab.
- » 12" digital touch screen operator display.
- » Swing out radiator grill.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Wheel chocks.
- » Hinged bonnet and exhaust module.
- » Oscillating hitch with stabilising lock cylinders.
- » Platform size 2,400mm wide x 4,000mm long.
- » Dual access ladders to either side of scissor basket.
- » 17% levelling ability for machine via levelling cylinders.
- » Digital inclinometer reading in cab.
- » Secondary steering and recovery brake release system.

- » Reverse camera.

#### Optional features:

- » Enclosed operator station with air conditioning.
- » Cab pressuriser.
- » DPF exhaust muffler on Tier 3.
- » Front suspension.
- » High speed fluid change.
- » Fire suppression system.
- » Automatic lubrication system.



### Specification Snapshot

GVM	23,400 kg
Rated capacity	5,000 kg AS1418.10 Group A, Type 1
Engine model	Cat C7.1 ACERT™ TIER 3
Gross power	SAE J1995 168 kW / 228 hp
Articulation	42.5°
Tyres	14.00 R20



## E10 Agitator 6m³

### Machine Application

Specialising in the transport of smaller batches of concrete to backfill voids, this agitator has an excellent top speed at full capacity improving cycle times and increasing production. Capable of onboard mixing and loading via chute or conveyor.

#### Standard features:

- » Cat powertrain.
- » All wheel drive with lock-up torque convertor.
- » ROPS/FOPS certified centre-mounted three seat cab [3 m high].
- » Tilting cab.
- » 12" digital touch screen operator display.
- » Swing out radiator grill.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Wheel chocks.
- » Hinged bonnet and exhaust module.
- » Oscillating hitch.
- » Secondary steering and recovery brake release system.
- » Electromagnetic retarder.
- » Electronic speed control.
- » 6m³ agitator bowl including 2x access covers and 2x empty bowl lift points.
- » Reverse camera.
- » Digital slump meter reading in cab.
- » Transit bowl speed 0-6 rpm.

- » Plant mix bowl speed 0-19 rpm.

- » Agitator bowl motor fitted with quick connect couplings.

#### Optional features:

- » Enclosed operator station with air conditioning.
- » Cab pressuriser.
- » DPF exhaust muffler on Tier 3.
- » Front suspension.
- » High speed fluid change.
- » Cat C7.1 TIER 4F engine arrangement.
- » Rear agitator bowl access ladder and platform.
- » Manual slump gauge at the rear of the machine.
- » High pressure washdown System.
- » Onboard chemical additive system.
- » Manual hand pump to add chemicals direct to bowl.
- » Steel mesh bowl guarding.
- » Discharge chute camera.
- » Fire suppression system.
- » Automatic lubrication system.



### Specification Snapshot

GVM	29,400 kg
Volume	6 m³
Engine model	Cat C7.1 ACERT™ TIER 3
Gross power	SAE J1995 168kW / 228 hp
Articulation	42.5°
Tyres	14.00 R20





## E10 Fuel & Lube

### Machine Application

Designed for in situ top up servicing of machines and equipment within the mine. Eliminates the need for production machines to leave remote work areas for minor maintenance work, reducing servicing time and traffic on haul routes.

#### Standard features:

- » Cat powertrain.
- » All wheel drive with lock-up torque convertor.
- » ROPS/FOPS certified centre-mounted three seat cab (3 m high).
- » Tilting cab.
- » 12" digital touch screen operator display.
- » Swing out radiator grill.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Wheel chocks.
- » Hinged bonnet and exhaust module.
- » Oscillating hitch.
- » Secondary steering and recovery brake release system.
- » Electromagnetic retarder.
- » Electronic speed control.
- » Provision for 1 x grease container.
- » Provision for 2 x 44 gal drums with 2 point lash down device.
- » Hose reel cabinet at rear of machine.

- » Fire extinguisher in rear hose reel cabinet.
- » 1 x 5,000L diesel fuel tank.
- » 4 x 300L oil tanks.
- » Reverse camera.

#### Optional features:

- » Enclosed operator station with air conditioning.
- » Cab pressuriser.
- » DPF exhaust muffler on Tier 3.
- » Front suspension.
- » High speed fluid change.
- » Cat C7.1 TIER 4F engine arrangement.
- » Fire suppression system.
- » Automatic lubrication system.
- » Tank capacities and configuration can be customised to suit application requirements - combined capacity up to 10,000L.

## E10 Water Cannon

### Machine Application

The dual application machine features a water cannon to wash down valuable ore fines, blast material hang ups, and fight fires. In addition, the side and rear water sprays suppress haul road dust and wash down internal surfaces of tunnels.

#### Standard features:

- » Cat powertrain.
- » All wheel drive with lock-up torque convertor.
- » ROPS/FOPS certified centre-mounted three seat cab (3 m high).
- » Tilting cab.
- » 12" digital touch screen operator display.
- » Swing out radiator grill.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Wheel chocks.
- » Hinged bonnet and exhaust module.
- » Oscillating hitch.
- » Secondary steering and recovery brake release system.
- » Electromagnetic retarder.
- » Electronic speed control.
- » Automatic boom pack up.
- » Water cannon on extendable boom with approx 8m reach.
- » Boom movement, 32° up, 10° down, 95° left and 95° right from centre.
- » Cameras - multiple viewing options available.

- » Boom and water cannon controlled by either tethered remote or in cab.
- » Water pressure approx 150 psi.
- » Water flow approx 2,700 l/min.
- » Water cannon nozzle size 38 mm (1 1/2").

#### Optional features:

- » Enclosed operator station with air conditioning.
- » Cab pressuriser.
- » DPF exhaust muffler on Tier 3.
- » Front suspension.
- » High speed fluid change.
- » Cat C7.1 TIER 4F engine arrangement.
- » Fire suppression system.
- » Automatic lubrication system.
- » Wireless remote controlled boom and water cannon.

### Specification Snapshot

GVM	24,750 kg
Diesel tank	5000 L
Engine model	Cat C7.1 ACERT™ TIER 3
Gross power	SAE J1995 168kW / 228 hp
Articulation	42.5°
Tyres	14.00 R20

### Specification Snapshot

GVM	28,660 kg
Water tank	8000 L
Engine model	Cat C7.1 ACERT™ TIER 3
Gross power	SAE J1995 168kW / 228 hp
Articulation	42.5°
Tyres	14.00 R20





# MED PULLER

## SAFE, LOW IMPACT EXTRACTIONS

### The fit-for-purpose mine extraction device

The Elphinstone Mine Extraction Device (MED) was invented to extract bogged or buried equipment without damaging the mine or negatively impacting production. Engineer certified, the MED has a pulling capacity of up to 360 Tonnes.

The MED has performed hundreds of successful extractions at a number of underground mining operations (both coal and hard rock) across Australia and internationally.

### Minimises disruptions to mining operations

Production disruptions are minimised by eliminating the need to deploy production equipment to assist in recoveries as well as minimising interactions with bogged or buried equipment.

The MED eliminates the need for traditional recovery methods that involve the use of other mobile equipment, which reduces the hazards associated with personnel working around mobile equipment in close quarters and allows other mining operations to continue relatively uninterrupted.

### What makes the MED so unique?

The Mine Extraction Device does not rely on traction like other systems. After the MED is towed into position, the boom is raised against the roof and the wheels are lowered on the floor. A bridle is interlocked onto the teeth of the MED racks. The racks are then pulled via hydraulic cylinders.

This is in contrast to using wheeled or tracked tow vehicles that can result in damage to the machines, the mine wall, floor or all of these in an attempted extraction process, all of which can add further delays to the restart of production.

### Insurance supports the proven MED system

The unique retrieval system has the support of numerous insurance companies with the recognition that if this system cannot retrieve a buried loader then the loader is not retrievable.

### Three power-packed levels of pulling capacity

The Mine Extraction Device is available in 150-tonne, 210-tonne, and 360-tonne capacities. The MED150, MED210, and MED360 were developed in line with industry growth.

In addition to the retrieval of buried equipment, the higher capacity models are also capable of extracting drill rods embedded in the rock face.

### Features Include:

- » Pulling capacity of up to 360 Tonnes.
- » The extendable boom allows use in a range of underground operations.
- » Easily towed into place.
- » Operating pressure (Max) 180 Bar, flow rate of 6-70 litres per minute.
- » Control pedestal and pilot valve.
- » Optional remote control.
- » Winch to assist rack positioning.
- » Cranes to assist positioning racks (MED360 only)







# NEW EG20 SIMPLE, ROBUST AND PRODUCTIVE

## Designed for comfort and productivity - all day

The EG20 enclosed cab has improved ergonomics, machine control adjustability and visibility. Incorporated in the design of the cab is a roll over protection system (ROPS) or falling object protection system (FOPS) with low vibration levels, reducing operator fatigue. Cab features include low-effort pedals, controls, adjustable implement controls, steering wheel angle, and seat. Improved leg room across the spine and additional storage areas including cup holders located on both sides of the cab enhances operator comfort.

## Easy-to-read instrument cluster

The centrally positioned digital instrument panel, with easy-to-read, high-visibility gauges and warning lamps, places vital machine information and diagnostic capability in direct view of the operator. Working in the dark is much easier with backlit transmission shifter and rocker switches.

## Machine safety with ground-level access

The EG20 is engineered to help protect the operator and others on the job site, featuring a ground-level isolation, laminated glass windows, door and seat belt park brake interlocks, visual and audible detection alarms, seat belt cutter, robust rear-guard, hydraulic brakes, e-stops, fire suppression actuators, front counterweight and more.

High-visibility green grab rails and steps for three-point contact, brake and reversing lights, alarms, and blade and rear-view cameras with dedicated display all combine to ensure a safe work environment. The ground level fuel fill system prevents the need to climb on the machine. An optional fast fill is also available at ground level.

## Drawbar, circle and moldboard

The EG20 drawbar is designed for high strength and optimum durability. The circle withstands high stress loads and raised wear surfaces prevent hardened circle teeth from wear against the drawbar. The moldboard provides optimal curvature and large throat clearance helping to move all material types quickly and efficiently. The blade lift cylinder accumulators assist in reducing blade bounce and damage to the blade components.

## EG20 Motor Grader

### Machine Application

Simple and robust, the EG20 smooths and maintains haul roads for increased productivity and reduced operational costs of the haul fleet. The EG20 utilises the Cat® 120 base machine with custom modifications for underground conditions.

### Standard features:

- » Cat powertrain with power shift countershaft transmission.
- » Low profile (2.64 m high) ROPS/FOPS certified enclosed cabin with airconditioning.
- » 3 piece wheel rims (24", 610 mm nominal diam.).
- » Wheel chocks.
- » Easy to read in-dash instrument cluster.
- » Rear radiator protection frame.
- » "Live Spindle" front axle design.
- » Conventional steering wheel and lever hydraulic implement controls.
- » Eight forward and six reverse gears for optimal productivity.
- » Reduce height of mold-board lift cylinders.
- » Reduce height of the exhaust outlet and air intake.
- » LED work lights.
- » Large front counterweight.

- » Turning circle inner/outer 60.2 / 235" 1530 / 5970mm.
- » Width over front tyres 98.2" 2495mm.

### Optional features:

- » Shortened wheel base.
- » Reduced width moldboard from 12' to 10' (3700 to 3048 mm).
- » Fire suppression system.
- » Automatic lubrication system.
- » Reverse camera.
- » Rear mounted ripper assembly.
- » Blade cameras.
- » Front work lights
- » C7.1 TIER 4F engine arrangement.



### Specification Snapshot

GVM	15,000 kg
Engine model	Cat C7.1 ACERT™ TIER 3
Gross power	SAE J1349 97 kW/130 hp
Frame articulation left/right	20°
Steering range left/right	50°
Tyres (Tubeless)	14.00 x 24 12 ply E2



# WR820 20-TONNE BASE PLATFORM

Designed for various underground mining applications, the Elphinstone WR820 chassis is a heavy-duty multipurpose platform with applications comprising a 10m<sup>3</sup> and 8m<sup>3</sup> agitator, and a 16000 L capacity water tank.

## Two cabin configurations available

Fitted with a standard open cabin, the WR820 is also available with an optional enclosed cabin with pressuriser and airconditioning (pictured above). The enclosed cabin features ergonomics for operator comfort, user-friendly intuitive controls, and excellent visibility.

The cabin includes the following features:

- » ROPS/FOPS certified design.
- » Air ride suspended seat standard.
- » Enclosed operator station available as an option, with climate-control and cabin pressurisation.
- » Seatbelt, 2-point retractable lap with optional occupancy indicator.
- » Emergency stop inside the cabin.

## Other key features

- » The modular ROPS/FOPS compliant cabin is resiliently mounted on the truck chassis, reducing vibration for greater comfort and a quieter ride.
- » Machine health monitoring system and alarm strategy provides a 3-tier warning and shutdown functionality.
- » Machine Isolation functions accessible at ground level.
- » Engine compression brake integrated with engine retarder for superior braking performance.
- » Ground level access to all service points and filters.
- » Interlock system detects the absence of the operator and applies the park brake.

Visit [elphinstone.com](http://elphinstone.com) to find out more.



## WR820 Water Tank

### Machine Application

Utilises water spray heads mounted at the rear and sides of the tank to suppress haul road dust and wash down internal surfaces of tunnels. The optional water cannon can be used to wet down ore stockpiles, draw points and to fight fires.

### Standard features:

- » Cat powertrain.
- » All wheel drive.
- » ROPS/FOPS certified one seat cab (2.5 m high).
- » Front oscillating axle.
- » Swing out radiator grill.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Wheel chocks.
- » Automatic retarder.
- » Variable water delivery system - varies the water output rate with ground speed to maintain a constant volume of water on the road regardless of ground speed.
- » Water flow control, water level and pressure on in cab control screen.
- » Automatic water pump shutdown when tank is empty.
- » 3 x water spray heads [1 x horizontal & 2 x vertical [1 x on each side of the truck]].
- » Manual 2.5" dump valve in water tank.

- » Water tank pump and hydraulic valves easily accessible for maintenance.
- » Thermal lagging material on turbo, exhaust pipe and muffler.
- » Secondary steering and recovery brake release system.

### Optional features:

- » Enclosed operator station with pressuriser and air conditioning.
- » Fire suppression system.
- » DPF exhaust muffler.
- » Water cannon (joystick controlled from cab).
- » Cameras - multiple viewing options available.



### Specification Snapshot

GVM	42,631 kg
Water capacity	16,000 L
Engine model	Cat C11 ACERT™ TIER 3
Gross power	SAE J1995 242kW / 325 hp
Articulation	42.5°
Tyres	18.00 R25





## **WR820 Agitator 10m³**

### Machine Application

Highly productive bulk transport of concrete to backfill voids, and transfer of shotcrete to shotcrete machines. Front suspension and increased braking performance allow the machine to travel at speeds equal to the production fleet increasing productivity.

#### Standard features:

- » Cat powertrain.
- » All wheel drive.
- » ROPS/FOPS certified one seat cab (2.5 m high). Front suspension.
- » Swing out radiator grill.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Wheel chocks.
- » Automatic retarder.
- » 10m³ agitator bowl including 2x access covers and 2x empty bowl lift points.
- » Digital slump meter gauge in cab display.
- » High performance heavy duty axles.
- » Agitator variable speed bowl controls in cab and manual pendant at rear of the machine.
- » Digital inclinometer in cab.
- » Agitator bowl motor fitted with connect couplings.
- » Thermal lagging material on turbo, exhaust pipe and muffler.

- » Secondary steering and recovery brake release system.
- » Transit bowl speed 0-8 rpm.
- » Plant mix bowl speed 0-19 rpm.

#### Optional features:

- » Analogue slump meter gauge at rear control panel.
- » Rear agitator bowl access ladder and platform.
- » Enclosed operator station with pressuriser and air conditioning.
- » Fire suppression system.
- » DPF exhaust muffler.
- » 235L water tank with water hose reel.
- » Automatic lubrication system.
- » 265L chemical tank.
- » Manual hand pump to add chemicals direct to bowl.
- » Steel mesh bowl guarding.
- » Storage rack for 2 x 20L rectangular drums.
- » Cameras - multiple viewing options available.

### **Specification Snapshot**

GVM	50,095 kg
Volume	10 m³
Engine model	Cat C11 ACERT™ TIER 3
Gross power	SAE J1995 242kW / 325 hp
Articulation	42.5°
Tyres	18.00 R25

## **WR820 Agitator 8m³**

### Machine Application

Specialising in large volume transport of concrete to backfill voids and transfer of shotcrete to shotcrete machines. The front oscillating axle maintains contact with the ground for increased traction while negotiating rough terrain.

#### Standard features:

- » Cat powertrain.
- » All wheel drive.
- » ROPS/FOPS certified one seat cab (2.5 m high).
- » Front oscillating axle.
- » Swing out radiator grill.
- » Bulkhead connections in hitch for hoses and harnesses.
- » Wheel chocks.
- » Automatic retarder.
- » 8m³ agitator bowl including 2x access covers and 2x empty bowl lift points.
- » Digital slump meter gauge in cab display.
- » Agitator variable speed bowl controls in cab and manual pendant at rear of the machine. Agitator bowl motor fitted with connect couplings.
- » Thermal lagging material on turbo, exhaust pipe and muffler.
- » Secondary steering and recovery brake release system.
- » Transit bowl speed 0-8 rpm.
- » Plant mix bowl speed 0-19 rpm.

#### Optional features:

- » Analogue slump meter gauge at rear control panel.
- » Rear agitator bowl access ladder and platform.
- » Enclosed operator station with pressuriser and air conditioning.
- » Fire suppression system.
- » DPF exhaust muffler.
- » 235L water tank with water hose reel.
- » Automatic lubrication system.
- » 265L chemical tank.
- » Manual hand pump to add chemicals direct to bowl.
- » Steel mesh bowl guarding.
- » Storage rack for 2 x 20L rectangular drums.
- » Cameras - multiple viewing options available.

### **Specification Snapshot**

GVM	42,200 kg
Volume	8 m³
Engine model	Cat C11 ACERT™ TIER 3
Gross power	SAE J1995 242kW / 325 hp
Articulation	42.5°
Tyres	18.00 R25





# HAULMAX 3900 EXTENDED HAUL TRUCK

The Haulmax 3900's 80 tonne nominal capacity payload management system, additional tyre capacity and braking capability makes it an ideal solution for extended distance haulage. With its narrow width, low centre of gravity, low ground pressure footprint, the Haulmax 3900 operates well in arduous conditions. Elphinstone have delivered over 120 Haulmax trucks via the global Caterpillar Dealer Network to customers in Australia, North America, Canada, Africa and South America where they are providing solutions as extended distance haul trucks, service trucks, low bed tow tractors, water trucks, and wet weather/ downhill haulers.

## 95% Genuine CAT components

The 3900 series haul truck incorporates a complete Caterpillar powertrain, and with 95% of all serviceable parts being genuine Cat components, customers are able to take full advantage of the local product support capabilities provided by the global Caterpillar dealer network. Elphinstone works closely with Caterpillar® to ensure matched power train components optimise longevity, reliability and mechanical availability, resulting in improved productivity and reduced operating costs.

## 80 tonne nominal payload capabilities

The 3900 Series Truck was developed to operate on haulage cycles of approximately 50km (30 miles). A narrower width means roads which cost considerably less to build and maintain. The longer the distance, the larger the cost saving.

## Payload management

The integrated Haulmax Payload and Tyre Pressure Monitoring System (TPMS) is designed to measure, record and display live data plus prevent overloading.

## Spacious two-person cab (ROPS/FOPS certified)

The 3900 features a large two-person cab, offering comfortable working space for both the operator and trainer or trainee. Resiliently mounted to the frame to reduce vibration and sound, the integral ROPS structure provides "five-sided protection" for the operator and passenger.

## Independent front suspension

The front suspension system and rear independently mounted 'A' frame axle assemblies combine with a long wheel base offering unrivalled levels of safety and comfort.

## Air suspension seats

Air suspension seats for both operator and passenger, are fully adjustable enhancing comfort with a cushioned upper high back, adjustable dampening with three settings, ride zone indicator and adjustable lumbar settings.

## Ergonomic cabin layout

The 3900 operator station is ergonomically designed for total machine control in a comfortable, productive and safe environment, minimising operator fatigue.

## Box-section chassis design

Incorporates castings in high-stress areas connected with full penetration continuous wrap-around welds.



## Specification Snapshot

GVM	135,000 kg
Engine model	Cat C27 ACERT™
Payload (nominal)	80 tonne
Gross power	SAE J1995 587 kW / 787 hp
Maximum speed	76.4 km/h (47.5 mph)
Height (top of standard exhaust)	4770 mm
Length**	14585 mm
Width (across mirrors)	4850 mm





### **Cat C27 engine with ACERT™ technology**

Reduces emissions during the combustion process by using advanced technology in the air and fuel systems, in conjunction with integrated electronics. Meets US EPA Tier 2 and European Union Stage II standards.

### **Application specific transmission**

The Cat mechanical drive power train and power shift transmission provides unmatched operating efficiency and control on steep grades in poor underfoot conditions and on haul roads with high rolling resistance.

### **Lock-up torque converter**

Combines maximum rimpull and cushioned shifting of torque converter drive with the efficiency and performance of direct drive. The lock-up torque converter engages at approximately 8 km/h (5 mph), delivering more power to the wheels.

### **Electronic control module (ECM)**

ECM uses advanced engine management software to monitor, control and protect the engine using self-diagnosing electronic sensors. The computerised system senses operating conditions and power requirements and adjusts the engine for peak performance and the most efficient operation at all times.

### **Instrument cluster**

Critical operating information on the 3900 is relayed via the Cat Data Link to five gauges, 18 LED indicator lights, and an LCD digital display.

### **Traction and control in slippery conditions**

Chassis and wheel base symmetry allows improved operator control in slippery underfoot conditions, with optimised weight distribution and dual rear axle drive-braking and traction control.

### **Suspension system**

Designed to handle mine site conditions enhancing a longer frame and service module life plus a more comfortable ride. Six independent self-contained, oil pneumatic, variable rebound suspension cylinders are designed to absorb shocks in the most severe applications.

### **Brake systems**

Hydraulically controlled dry front and rear oilcooled multiple disc brakes provide exceptional, fade-resistant braking and retarding for maximum performance and productivity in all mine site conditions.

### **Engine shutoff switch**

A secondary engine shutoff switch is located at ground level along with a hood tilt switch and other electrical isolators.

### **Designed with safety as a priority**

Access ladders, fire suppression, LED light options, and optional camera at the rear ensure a safe work environment for the operator.

### **Serviceability equals increased uptime**

Easy access to daily service points simplifies servicing and reduces time spent on regular maintenance. Enhanced serviceability and extended 500-hour engine service intervals are designed to increase machine availability and productivity.

### **Maintenance platform**

Easy stairway access to engine, air filters and radiator. Platform access for hydraulics and steering. Ground level access allows convenient servicing to tanks, filters, evacuation points, battery disconnect and engine shutdown.

### **Global Dealer Network**

Haulmax trucks are sold and supported via the global Caterpillar Dealer Network providing unparalleled sales and aftermarket support. Elphinstone endeavours to provide the latest technology in all products. Design updates are constantly made to ensure industry expectations of reliability, safety and operator comfort are achieved.



# OVER 45 YEARS IN THE MINING INDUSTRY.

Elphinstone Pty Ltd is an established Caterpillar OEM Solutions customer with over 45 years' experience in the mining industry.

Elphinstone specialises in the design, manufacture and support of quality equipment for the global underground and surface mining industries.

The Elphinstone range of products combines practical design, the latest technology and quality manufacturing to ensure reliable performance.

The current product range includes specialised underground support vehicles, mine extraction devices, extended distance off-highway haulage trucks and water tanks customised to suit Caterpillar articulated trucks.

All Elphinstone products, technical assistance, support, and access to spare parts are available through the global Cat® dealer network with additional support from the Elphinstone regional sales and support team.

## ELPHINSTONE

For more complete information on Elphinstone products, dealer services, and industry solutions, visit [www.elphinstone.com](http://www.elphinstone.com) or contact your local Cat® dealer.

Material and specifications are subject to change without notice. Featured machines in photos may include additional equipment.

Elphinstone and their respective logos, as well as corporate and product identity used herein, are trademarks of Elphinstone and may not be used without permission.

© 2025 Elphinstone. All rights reserved.  
Made in Australia for export.



Version 21 (03-2025)